

SERVICE BULLETIN



SERVICE DEPARTMENT
DODGE
DIVISION OF CHRYSLER CORPORATION

TO ALL DIRECT DEALERS AND DEALERS:

The fuel injection pumps used in Diesel engines contain, of necessity, some highly precision parts, that is, parts that are manufactured to very close limits.

It is accordingly extremely important that every precaution be taken to prevent dust and other foreign abrasives from reaching these units, as even a slight amount of wear will affect the operation of the pump.

Such precautions include, first, the use of clean fuel, oil free of dirt, water and other impurities and second, the cleaning or replacing of both fuel filter elements at frequent intervals - under no circumstances should the truck be operated unless BOTH the 1st stage and 2nd stage filters are intact and complete with proper elements.

Whenever it is found necessary to replace any of the fuel injection pump units or parts, the pump should be disassembled sufficiently to thoroughly clean it, for in most cases, such replacement is necessitated by wear and if the pump is not cleaned, the abrasives which have been responsible will remain in the pump and cause further difficulty. Also, at the same time, the fuel filter elements should be cleaned or replaced.

Enter this bulletin number and subject in your Dodge Truck Shop Manual under Group - ENGINE.

B. B. SETTLE
Director of Service
DODGE DIVISION

Jan. 19, 1942

No. D-108

ENGINE

FUEL INJECTION

PUMP

--

ALL DIESEL

TRUCKS

7009

Prtd. in U.S.A.

14763